



December 9, 1992

GEOTECHNICAL, ENVIRONMENTAL & CONSTRUCTION MATERIALS CONSULTANTS

Guilford County
Department of Emergency Services
P.O. Box 18807
Greensboro, NC 27419

Attention:

Ms. Kelly Gage

Toxic & Health Hazard Specialist

Subject:

Report of Limited Ground-Water Assessment

Taco Bell Site

3742 Battleground Avenue Greensboro, North Carolina

Law Engineering Job No. 259-00194-03

Dear Ms. Gage:

At the request of Mr. James Koutris, Construction Manager for Taco Bell Corporation, Law Engineering is submitting this Report of Limited Ground-Water Assessment for the subject site. The purpose of our services was to assess the site for evidence of environmental contamination caused by a former underground storage tank (UST) system. This report includes a description of the site activities, the results obtained, and our conclusions and recommendations.

Please contact us if you have any questions concerning this report.

Sincerely,

LAW ENGINEERING

Scott C. Veenstra Project Geologist

James D. Rudder, Jr., P.G.

Principal Geologist



November 27, 1992

GEOTECHNICAL, ENVIRONMENTAL & CONSTRUCTION MATERIALS CONSULTANTS

Taco Bell Corporation 2303 W. Meadowview Road Suite 41 Greensboro, NC 27407

Attention:

Mr. James N. Koutris Construction Manager

Subject:

Report of Limited Ground-Water Assessment

Taco Bell Site

3742 Battleground Avenue Greensboro, North Carolina

Law Engineering Job No. 259-00194-03

Dear Mr. Koutris:

As authorized by your acceptance of our Proposal No. PGB-446E, Law Engineering is pleased to submit this Report of Limited Ground-Water Assessment for the subject site. The purpose of our services was to assess the site for evidence of environmental contamination caused by a former underground storage tank (UST) system. This report includes a description of the site activities, the results obtained, and our conclusions and recommendations.

Law Engineering appreciates the opportunity to serve as your environmental consultant on this project. We will contact you within several days to see if you have any questions concerning this report.

Sincerely,

LAW ENGINEERING

Scott C. Veenstra

Project Geologist/Engineer

James D. Rudder / Jr., P.G.

Principal Geologist

TABLE OF CONTENTS

1.0	INTROI	OUCTIO	. ис		•	• •		•	-	•	•	•	•	•	•	•	•	•	•	•	•	1
2.0	CONTRA	ACTED	SCOPE	OF	SE	RVIC	ES	•		•	•	•		•	•	•		•	•		•	1
3.0	FIELD	ACTIV	/ITIES	•	•				•		•	•			•	•	•	•	•	•	•	2
	3.1	Soil	Borin	g ar	nd	Samp	olin	g	•	•	•	•	•		•	•	•	•	•	•	•	2
	3.2	Monit	toring	Wel	<u> 1</u>	Inst	all	ati	Lor	į	•	•	•		•		•	•	•	•	•	3
	3.3	Monit	toring	Wel	1	Deve	lop	me <u>r</u>	<u>ıt</u>	•	•	•	•		•	•	•	•	•	•	•	4
	3.4	Monit	toring	Wel	<u> 1</u>	Samp	olin	g				•	•				•	•	•	•	•	4
4.0	ANALY'	TICAL	RESUL	TS	•			•	•	•	•	•		•	•	•	•	•	•	•	•	5
	4.1	Resul	lts of	Ana	aly	ses	of	We]	1,1	Sa	mp	le	s	•		•			•	•	•	5
5.0	QUALI	ry ass	SURANC	E/QU	JAL	ITY	CON	TRO	ΣL	RE	su	JL.T	S	•			•				•	5
6.0	CONCL	JSIONS	S AND	RECO	MMC	END	ATIO	NS						•	•		•		•		•	5
7.0	QUALI	FICATI	ON OF	REI	POR	T.		•						•	•		•				•	5
TABI	LES																					
FIG	URES																					
APP	ENDIX																					



1.0 INTRODUCTION

The subject site is located at 3742 Battleground Avenue in Greensboro, North Carolina. Richardson Turner Construction Company (RTC) was previously contracted by Taco Bell to construct a Taco Bell restaurant on the site. During construction of an on-site retention pond three underground storage tanks (USTs) were discovered. These USTs were subsequently removed from their original locations by a subcontractor to RTC.

Taco Bell Corporation retained Barrow Backhoe Company to dispose of the USTs, excavate petroleum hydrocarbon-containing soil associated with the USTs, and temporarily stockpile the excavated soil on site. Taco Bell contracted Law Engineering to monitor the excavation activities, perform soil sampling, and perform a preliminary ground-water assessment (Law Job No. 259-00194-02).

Based on the detected concentrations of benzene in the ground water beneath the site, the Guilford County Department of Emergency Services has requested that Taco Bell conduct additional quarterly sampling of the ground water.

The project information has been provided from discussions between Mr. James Koutris of Taco Bell and Mr. Scott Veenstra and Mr. Brian Maas of Law Engineering.

2.0 CONTRACTED SCOPE OF SERVICES

Law Engineering was contracted to complete the following scope of services:

- Drill one soil boring to an approximate depth of 20 feet below grade using an auger drill rig. The boring would be drilled in the vicinity of the former temporary monitoring well MW-1.
- During the drilling of the auger boring soil samples would be collected with decontaminated split-spoon samplers every five feet in the material above the ground-water table (e.g. 3.5 to 5 feet, 8.5 to 10 feet) in general accordance with ASTM D1586.

The soil samples would be screened with an organic vapor analyzer (OVA) and the measurement recorded.

 Install one ground-water monitoring well in the boring described above. The well would be constructed with 2inch I.D. schedule 40 PVC screen and casing. The screened interval would be constructed of slotted PVC having slot



widths of 0.01 inches. The screened interval would be 15 feet in length and would be installed to intersect the elevation of the ground-water table at the time of drilling.

- Develop, purge and sample the newly-installed well. The ground-water sample collected would be shipped to Law Environmental National Laboratories (LENL) for analysis for benzene, toluene, ethylbenzene, and xylenes (BTEX) using the EPA Method 602.
- Prepare a written report describing our activities, the results obtained, and our conclusions and recommendations.
- Conduct an additional quarterly sample collection from the monitoring well approximately three months after the first sampling event (to be completed in February 1993).
- Prepare a written report for the second quarterly sampling event, describing our activities, the results obtained, and our conclusions and recommendations (to be completed in February 1993).

We implemented the above scope of services on October 27, 1992 based on your written authorization accepting Law Engineering Proposal No. PGB-446E2.

3.0 FIELD ACTIVITIES

3.1 Soil Boring and Sampling

Law Engineering personnel drilled one soil boring (MW-1) to a depth of approximately 23.5 feet below grade. The soil boring was drilled using a truck-mounted drilling rig equipped with 6 1/4-inch I.D. hollow stem augers. To prevent cross contamination, the drilling equipment was steam cleaned prior to commencing activities at the drilling location. The split spoon sampler was decontaminated prior to each use utilizing high pressure steam cleaning (using potable water).

The boring was completed to a depth of 23.5 feet below the ground surface. The termination depth of the boring was selected based on consideration of the depth to ground water, as indicated by soil moisture conditions, auger cuttings, observations of water within the borehole, and the objectives stated above in the scope of services.



Soil samples were collected at five-foot intervals starting at a depth of 3.5 feet below the ground surface. The samples were collected using a split-spoon sampler 18 inches long having an inside diameter of 1 3/4-inches. The soil sampling methodology was performed in general accordance with ASTM D-1586. Representative samples were classified in the field by Law Engineering's on-site field personnel. Soil Test Boring Records were completed for the boring and are contained in the Appendix.

Representative portions of each soil sample obtained from the boring were transferred into a new, clean one-quart capacity zip-lock baggy (approximately half full), and the baggy was placed in a warm location. Approximately ten minutes after the time of collection the baggy was opened slightly and the probe of a Century 128 Organic Vapor Analyzer inserted. The baggy was immediately resealed using finger pressure. The meter of the OVA was monitored and the reading recorded. An OVA is useful only as a screening tool in evaluating the absence or presence of volatile organic compounds (VOCs), and should not be relied upon to quantify VOCs in soil samples. The results of the OVA screening did not detect VOCs in the soil samples collected from boring MW-1.

3.2 Monitoring Well Installation

After completion of the soil boring, the boring was converted to a monitoring well having a total depth of 21 feet below the ground surface. The well was installed as a Type II ground-water monitoring well constructed with 2-inch I.D. Schedule 40 PVC flush-threaded casing and screen. The PVC screen and casing were lowered through the annulus of the augers to the appropriate depth. A 15-foot slotted well screen with machined 0.010-inch slot widths was installed at the bottom of the well. A threaded bottom plug was placed at the bottom of the screened interval.

A solid section of PVC riser pipe was placed above the screened interval and extended to a point just below grade. The annular space around the well was filled with a washed and graded medium sand to approximately two feet above the screen.

A minimum one-foot thick seal of bentonite pellets was placed immediately above the sand pack. After placement in the well, the bentonite pellets were hydrated by applying approximately ten gallons of potable (tap) water and waiting approximately 30 minutes.

After hydrating the bentonite pellets, a bentonite/neat cement mixture containing approximately four percent bentonite was pumped down the hole to fill the annulus of the boring from the bentonite cap to the ground surface. A flush-mounted steel cover was



installed over the well. The well was equipped with a lockable, water-tight well cap. The general construction details for the well are shown on the Boring Log and Well Installation Diagram in the Appendix. A copy of the monitoring well construction permit issued by the State of North Carolina Division of Environmental Management, Groundwater Section is included in the Appendix.

3.3 Monitoring Well Development

A minimum of 24 hours after installation, the well was developed by evacuating approximately five well volumes using a disposable one-liter capacity teflon bailer. The well was developed to achieve two objectives: 1) to remove sand, silt and other fine sediments which may have entered the well during its construction; and 2) to develop the sandpack surrounding the well's screened interval.

During development the pH of the development water from the well was monitored. Development continued until the pH stabilized and the water cleared of fine sediments. The stabilized pH measured was 6.9 standard units.

3.4 Monitoring Well Sampling

A minimum of 24 hours after development, the well was purged until the pH stabilized by removing at least five well volumes. Purging was accomplished using the disposable one-liter capacity teflon bailer. Ground-water samples were collected from the well immediately after the well was purged. The pH of the collected ground-water sample was 6.9 standard units.

Immediately after collection, each ground-water sample was transferred from the teflon bailer into three 40 milliliter (ml) clean, glass containers equipped with teflon-lined screw-caps. New disposable vinyl gloves were utilized in the sample transfer. The sample containers were completely filled with sample to eliminate headspace.

After being filled, each sample container was labeled with the job name and number, the time and date of sample collection, the analyses to be performed, and the presence or absence of preservative. The filled sample containers were placed into a new one-quart capacity zip-lock baggy. The baggy containing the filled sample containers was then placed into a cooler containing ice and cooled to approximately 4° Centigrade. The chain of custody was initiated. At the end of each sampling day the cooler containing samples was shipped via overnight express delivery to LENL in Kennesaw, Georgia.



4.0 ANALYTICAL RESULTS

4.1 Results of Analyses of Well Samples

The newly-installed ground-water monitoring well was sampled on November 6, 1992. The samples were analyzed by LENL for BTEX using the EPA Method 602. Table 1 presents a summary of the analytical results. All data results were reported as non-detected for BTEX concentrations.

5.0 QUALITY ASSURANCE/QUALITY CONTROL RESULTS

No duplicate ground-water samples were requested in the contracted scope of services, and none were collected in the field. No trip blanks were analyzed with the collected ground-water sample.

6.0 CONCLUSIONS AND RECOMMENDATIONS

The ground-water sample collected from ground-water monitoring well MW-1 did not contain detectable concentrations of benzene, ethylbenzene, toluene or xylenes in excess of the analytical method practical quantification limits. The analytical method practical quantification limits were one part per billion (ppb) for benzene, ethylbenzene, and toluene and two ppb for xylenes. Based on the analytical results, it does not appear that the former USTs at the Taco Bell location have released petroleum hydrocarbons into the subsurface which have impacted the ground water.

Based on the non-detection of BTEX concentrations in the collected ground-water sample, Law Engineering recommends that the second quarterly sample collection and analysis be implemented to confirm the data obtained during this sampling event.

7.0 QUALIFICATION OF REPORT

The activities and evaluative approaches used in this assessment are consistent with those normally employed in hydrogeological assessments and waste management projects of this type. Our evaluation of site conditions has been based on our understanding of the site and project information, and the data obtained from the site assessment activities performed to date at the subject site. The primary objective was to perform sufficient work to determine if ground-water contamination exists at the subject site.

TABLES

TABLE 1


VOLATILE COMPOUNDS DETECTED IN GROUND-WATER MONITOR THE WELLS IN PPM

Taco Bell Corporation 3742 Battleground Avenue Greensboro, North Carolina Law Engineering Job No. 259-00194-03


Well No.	Benzene	Ethylbenzene	Toluene	Xylenes	Total BTEX
MW-1	ND	ND	ND	ND	ND

ND = Not Detected
BTEX = Benzene, Toluene, Ethylbenzene, Xylenes
ppm = Parts Per Million

FIGURES



BATTLEGROUND AVENUE



LEGEND



MW-1

' MONITORING WELL

NOT TO SCALE

FORMER UST LOCATION

REF: FIELD NOTES BY LAW ENGINEERING

PERSONNEL



LAV ENGINEERING GREENSBORD, NORTH CAROLINA

MONITORING WELL LOCATION
TACO BELL

GREENSBORD, NORTH CAROLINA

JOB NO. 259-00194-03

FIGURE 2

APPENDIX

LABORATORY DATA REPORT



NATIONAL LABORATORIES DIVISION 300 CHASTAIN CENTER BLVD. SUITE 315 KENNESAW, GEORGIA 30144 404-426-4309 FAX 426-0243

November 12, 1992

Law Engineering, Inc. 7347 J. West Friendly Ave. Greensboro, NC 27410

Attention: Scott Veenstra

LE Job Number: 259-00194-01

Subject: Chemical analysis of samples received on 11/09/92.

Dear Mr. Veenstra:

Law Environmental National Laboratories has completed its analysis of your samples and reports the results on the following pages. These results related only to the contents of the samples as submitted. This report shall not be reproduced except in full without the approval of Law Environmental National Laboratories.

If there are any questions, please do not hesitate to contact us.

Sincerely,

LAW, ENVIRONMENTAL NATL LABS

Linda Harris

Hydrocarbon Laboratory Supervisor

Attachment: Data Report

Invoice

LAW ENVIRONMENTAL NATIONAL LABORATORIES TEST DATA REPORT

Date 11/14/92 Page 1

--- Project Information ---

Lab Number : 62-5014-01

Project No.: 259-00194-01

Cust. No. :

Project Name : TACO BELL MW

Manager: SCOTT VEENSTRA

--- Sample Information ---

Station ID : MW-1

Matrix : W

Type : GRAB

Collector : JRE

Sampled Date/Time : 11/06/92 13:00 Received Date/Time : 11/09/92 09:15

Received From/By : JRE/ST

Chain of Custody: 14807

Number of Containers: 3

Remarks :

--- Test Data ---

Parameter	. Method	Units	PQL	Results	Test Date	Anal
SERIES 15000						
Benzene	EPA 602	ug/l	1.0	ND	11/12/92	DLM
Toluene	EPA 602	ug/l	1.0	ИĎ	11/12/92	DLM
Ethylbenzene	EPA 602	ug/l	1.0	ND	11/12/92	DLM
Xylene, Total	EPA 602	ug/l	2.0	ND	11/12/92	DLM
SCREENING FOR BTEX RESULTS						
SCREENING FOR BTEX				NA	11/10/92	OR

Signed Linda Haum

LAW ENVIRONMENTAL, INC. NATIONAL LABORATORY 112 TOWNPARK DRIVE KENNESAW, GEORGIA 30144 (404) 421-3306

LAW ENVIRONMENTAL, INC. CHAIN OF

CHAIN OF CUSTODY RECORD

NAME OF FACILITY: _ STREET ADDRESS: _

SAMPLING

CITY / STATE:

14807

ZP

	がいかが		REMARKS	SLIDGE S
	ONIGHT AND TELECON COLLEGE ACCOUNT AND THE SHAWEN TO LABORATION TO PINK COPY RETAINED BY LABORATORY.			
1.8.4.5	(SIGNATURE) (SIGNATURE)	-	(SIGNATURE)	11/2/1/ 7/1/
1 2 2 2				1 02 1/12
DATE / TIME	DATE / TIME RELINGUISHED BY: RECEIVED BY RECEIVED BY	PA	:0 BY:	DATE / TIME RECEIVED BY:
2.5014-01		3 X		1-MM
FOR LAB	0 10 8 00 10 10 10 10 10 10 10 10 10 10 10 10	SILON	ESCRIPTION	SAMPLE STATION DESCRIPTION
		N JATO1 NATWOO		269-11
	W. siele. 1.03 (0).	NERS NO. OF	SAMPLERS INITIALS (PRINT)	+ Grano
	345		HOLOT PLAGE	MN

Date:

For Law Environmental National Lab Use Only

Inspected By:

Are Custody Seals Present? Yes No No Are Custody Seals Intact? Yes No NA

OTHER - NA

SOIL / SEDIMENT - SO



FORM COMPLETED BY:

LAW ENVIRONMENTAL **NATIONAL LABORATORIES**

KENNESAW REQUEST FOR ANALYSIS **HYDROCARBON LAB**

PROJECT NAME: TACO Bell COG#:	_
PROJECT #: 259-00/94TASK #: 01 PROJECT MGR: South Centre	ز_
HYDROCARBON (CIRCLE ANALYSES REQUESTED)	•
TURNAROUND TIME: STANDARD (1 WEEK) RUSH (INCURS RUSH FEE)	
SAMPLE I.D.: NW-/ days	
SAMPLE I.D.: MW-/ days	
BTEX Water/Soil 602 8020	
BTEX + MTBE 602 8020	
IPE 602 8020	
Petroleum Hydrocarbons, IR - EPA 418.1	
Oil & Grease 9070 9071 (Soil Only)	
Polynuclear Aromatic Hydrocarbons (PAH) 610 8100	
Petroleum Hydrocarbons, Volatile - CAL-DHS	
Petroleum Hydrocarbons, Semi-Volatile - CAL-DHS	
Petroleum Hydrocarbons, Volatile - EPA 5030/8015M	
Petroleum Hydrocarbons, Volatile - 5030/SF BAY	
Petroleum Hydrocarbons, Semi-Volatile - 3550/SF BAY	
Petroleum Hydrocarbons, GRO - TENN/5030	
Petroleum Hydrocarbons, DRO - TENN	
Petroleum Hydrocarbons, Volatile - IOWA/5030	
Petroleum Hydrocarbons, Semi-Volatile - IOWA	
Petroleum Hydrocarbons, Gas/Diesel - EPA 8015M/VA	
Petroleum Hydrocarbons, IR - WTPH-418.1M/WA	
Petroleum Hydrocarbons, Volatile - WTPH-G/WA	
Petroleum Hydrocarbons, Semi Volatile - WTPH-D/WA	
FORM COMPLETED BY: 11/2-9-	つ

LENL#: (07.5014-01 DATE: 11/9) PROJECT NAME: TOCO BELL MW PROJECT #: 259-00194-01 A: PRELIMINARY EXAMINATION: Date shipment was opened: _____ 11/9/97 1. Did shipment come with a shipping air bill? N NA 2. If YES, document carrier and air bill # FX # 48867 78702 3. Were custody seals present on samples? 4. Were custody seals intact? 5. Were custody papers filled out properly? 6. Were custody papers signed? 7. Are sampling time(s) present? 8. Are sampling date(s) present?_____ 9. Type of packing and ice used. due use / bubble wrap B: LOGIN-IN PHASE Date samples were logged-in: 11 9 97 1. Did all bottles arrive intact? 2. Did all bottle labels agree with custody papers? 3. Were proper containers used for requested test? 4. Were correct preservatives added for requested test?______ 5. Was sufficient sample received for requested test? COMMENTS: -No Trip Blk. rec.d ______Processed By:___ 5T C: CORRECTIVE ACTION: COMMENTS: INITIALS SAMPLE CONTROL COORDINATOR SAMPLE CONTROL SUPERVISOR

SAMPLE RECEIPT AND NON-CONFORMANCE FORM

MONITORING WELL CONSTRUCTION PERMIT



State of North Carolina Department of Environment, Health and Natural Resources

Winston-Salem Regional Office

James G. Martin, Governor William W. Cobey, Jr., Secretary Margaret Plemmons Foster Regional Manager

DIVISION OF ENVIRONMENTAL MANAGEMENT GROUNDWATER SECTION

November 3, 1992

Taco Bell Corporation 2303 W. Meadowview Road Suite 41 Greensboro, NC 27407

SUBJECT: MONITOR WELL CONSTRUCTION

PERMIT NO. 40-1011-WM-0488

GUILFORD COUNTY

FILE NAME: Taco Bell

Dear Sir:

In accordance with your application received October 26, 1992, we are forwarding herewith Monitor Well Construction Permit No. 40-1011-WM-0488 for the construction of one monitor well in the Charlotte Belt Hydrogeologic Unit.

Henceforth, correspondence and data relating to this well shall be designated as specified in the subject heading above.

This Permit will be effective from the date of its issuance and shall be subject to the conditions and limitations as specified therein.

Sincerely,

Sherri V. Knight

Groundwater Supervisor

SheniV. Knight

LDC/ahl Enclosure

cc: Groundwater Section - Central Office
Guilford County Division of Emergency

Guilford County Division of Emergency Management

WSRO Files

Law Engineering

NORTH CAROLINA

ENVIRONMENTAL MANAGEMENT COMMISSION

DEPARTMENT OF ENVIRONMENT, HEALTH AND NATURAL RESOURCES

PERMIT FOR THE CONSTRUCTION OF

A MONITOR WELL OR WELL SYSTEM

In accordance with the provisions of Article 7, Chapter 87, North Carolina General Statutes, and other applicable Laws, Rules, and Regulations.

PERMISSION IS HEREBY GRANTED TO

Taco Bell Corporation

FOR THE CONSTRUCTION OF ONE MONITOR WELL OR MORE AS NEEDED in the Charlotte Belt Hydrogeologic unit located at 3742 Battleground Avenue, Greensboro, North Carolina in Guilford County in accordance with the application dated October 22, 1992, and in conformity with the specifications and supporting data, all of which are filed with the Department of Environment, Health and Natural Resources and are considered a part of this Permit.

This Permit is for well construction only, and does not waive any provisions or requirements or any other applicable laws or regulations.

Construction of a well under this Permit shall be in compliance with the North Carolina Well Construction Regulations and Standards, and any other laws and regulations pertaining to well construction.

This Permit will be effective from the date of its issuance until the site assessment has been completed, and shall be subject to other specified conditions, limitations or exceptions as follows:

- Written permission must be obtained from the property owner prior to construction of the well.
- 2. A permanent identification plate with the date of construction, depth of well, screen interval, depth of grout, drilling contractor, and his registration number shall be attached to the well head or the outer protective steel casing.

Permit No. 40-1011-WM-0488
Page two

- 3. The well construction completion form and all water quality data are to be submitted to the Central Office of the Groundwater Section P. O. Box 29535, Raleigh, North Carolina 27611.
- 4. All laboratory analysis of Groundwater samples collected from the permitted monitor well are to be submitted to North Carolina Department of Environment, Health, and Natural Resources, Groundwater Section, P. O. Box 29535, Raleigh, N. C. 27611 with a copy to the North Carolina Department of Environment, Health and Natural Resources, Groundwater Section, 8025 North Point Boulevard, Suite 100, Winston-Salem, N. C. 27106 within 60 days of well completion, and quarterly thereafter.
- 5. All additional investigative findings in relation to the pollution sources being monitored, as indicated under "Additional Information" of form GW-22M ("Item J" of form GW-22B) of permit application, are to be submitted to North Carolina Department of Environment, Health and Natural Resources, Groundwater Section, P. O. Box 29535, Raleigh, N. C. 27611 with a copy to North Carolina Department of Environment, Health, and Natural Resources, Groundwater Section, 8025 North Point Boulevard, Suite 100, Winston-Salem, N. C. 27106 within 60 days of well completion, and quarterly thereafter.
- 6. The well shall be afforded a means of protection against vandalism, damage, or unauthorized use.
- 7. When any monitor well is no longer useful for its intended purpose, it shall be abandoned in compliance with North Carolina Administrative Code 15. 2C.0113 and a well abandonment form sent to the North Carolina Department of Environment, Health, and Natural Resources, Groundwater Section, P. O. Box 29535, Raleigh, N. C. 27611 with a copy to North Carolina Department of Environment, Health and Natural Resources, Groundwater Section, 8025 North Point Boulevard, Suite 100, Winston-Salem, N. C. 27106.

Permit No. 40-1011-WM-0488
Page three

- 8. The monitor well shall be constructed in accordance with the Groundwater Section's recommended construction details as outlined in attachment #1.
- 9. A county monitor well construction permit shall be required by the county health departments where applicable. In Forsyth County, contact the Forsyth County Health Department, Division of Environmental Health, P.O. Box 686, Winston-Salem, NC 27102-0686.
- 10. If additional monitor wells, not shown on the location diagram, need to be constructed, a map showing the proposed location shall be submitted to the Winston-Salem Regional Office, 8025 North Point Blvd., Suite 100, Winston-Salem, NC 27106.

Permit issued this the 3rd day of November 1992


FOR THE NORTH CAROLINA ENVIRONMENTAL MANAGEMENT COMMISSION

Larry D. Coble, Regional Supervisor Division of Environmental Management

By Authority of the Environmental Management Commission

Permit No. 40-1011-WM-0488

SOIL TEST BORING LOG AND MONITORING WELL COMPLETION DIAGRAM



SEE KEY SHEET FOR EXPLANATION OF SYMBOLS AND ABBREVIATIONS USED ABOVE BORING NUMBER

DATE DRILLED

October 27, 1992

PROJECT NUMBER 259-00194-01

PROJECT

TACO BELL

PAGE 1 OF 1

LAW ENGINEERING

GROUND-VATER MONITORING VELL INSTALLATION RECORD

JOB NAME _Taco_Bell	JOB NUMBER _259-00194-03
VELL NUMBER MW-1	GROUND SURFACE ELEVATION
LOCATION See Well Location Figure	
INSTALLATION DATE October 27, 199	
GROUND SURFACE	COVER ASSEABLY VITH READVEABLE STEEL COVER
LOCKABLE PVC CAP	
GROUT	DEPTH TO BASE OF
10 - INCH BORING	GROUT SEAL.
2 - INCH PVC PIPE	DEPTH TO TOP OF SAND BACKFILL
•	5 ft
BENTONITE SEAL	TOTAL DEPTH OF VELL
(1.0 FT THICK AINIAUA)	23.5 ft
SAND	DEPTH OF
PVC SCREEN	PVC SCREEN
(SLOT SIZE B.BIB INCH)	6 to 21 ft
CAP	
CVb	

NOTE: ALL PVC PIPE JOINTS

HAVE SCREV CONNECTORS